

Electrical

Electrical supply: 110-120 V AC, single phase 60 Hz
 Rated power: 1400 W
 Motor type: Dyson digital motor. Switched reluctance brushless
 Motor speed: 81,000 rpm
 Heater type: None
 Standby power consumption: 1 W
 Energy consumption per dry: 0.00468 kWh

Construction

Polycarbonate-ABS casing with homogenous anti-microbial additive
 Color finish: Metallic steel finish PC-ABS
 Anti-microbially integrated external plastics, seals and air ducts
 Galvanized steel back plate / mounting bracket
 Tamper-proof T30 type exterior screws
 Water ingress protection to IPX5

Filtration

HEPA filter with anti-microbial coating
 99.97% particulate efficiency < 99.9% bacterial removal

Operation

Touch-free infra-red activation
 Hand dry time: 12 seconds (measured to method defined by National Sanitation Foundation protocol P.335)
 Airspeed output: 400 mph
 Operating airflow: 68 CFM
 Rated operating noise power: 85 dB(A)

Logistics

Serial number prefix: A04-US
 Single unit order code: 14225-01
 Unit weight: 22 lb
 Packaged weight: 28.7 lb
 Packaged dimensions: 29.1" x 14.2" x 12.2"
 Pallet count: 13
 Pallet type: US
 Unit barcode: 879957002210

Standard warranty

5 year parts, 1 year labor limited

Product Certification

ETL listed in accordance with UL 507
 ADA Compliant

*Recommended installation heights measured from floor	Male	Female	Child or Disabled
x To top of machine	41.25"	38.25"	34.25"
y To mounting bracket screw	39.0"	36.0"	32.0"
z To bottom of machine	15.0"	12.0"	8.0"

Manufactured materials

Plastic: ABS, PC/ABS, PC, PP (+ PPGF and PPTF), PET-TS
 Thermoset (BMC/DMC), PEEK
 Rubber: Styrene, butadiene, EPDM
 Metal: Stainless steel, galvanized steel, zinc diecast alloy brass

For further information please contact Dyson at
1-888-DYSON-AB or email any questions to
airbladeinfo@dyson.com

