

KEEP IT CLEAN



EXCEL HAND DRYER WALL GUARDS

Wall Guards are designed specifically to fit securely underneath your Excel hand dryers, protecting your walls from water droplets that can be blown off wet hands by the powerful air stream of our high-speed hand dryers.

EXCEL HAND DRYER WALL GUARD




WHITE WALL GUARD



PART #89W



Microban's cutting edge antimicrobial coating product protection guards surfaces from the growth of bacteria, mold and mildew that can cause stains, odors and degradation of the surface.



Recommended location of adhesive strips

Part ID Description

ANTI-MICROBIAL WALL GUARDS

89W	Microban Wall Guard - White	2 Wall Guards/Set*
-----	-----------------------------	--------------------

*Set: 1 box of 2 wall guards

SPECIFICATIONS

Qty: 2 per set

Size: 31 3/4" x 15 3/4" x 1/16"

Weight: 4 lbs. per set

INSTALLATION:

Mounted with 4 strips of construction grade 3M adhesive tape (included)

MATERIALS

89W: Microban anti-microbial plastic: White

INSTALLATION INSTRUCTIONS

1. Clean the wall surface with ISOPROPYL ALCOHOL prior to installation and make sure that the surface is dry and free of any dust and debris.
 2. Center the Wall Guard underneath the hand dryer so that the top of the Wall Guard is 1" below the bottom of the dryer.
 3. Carefully measure and mark the wall surface for placement of the Wall Guard with a pencil or temporary marker.
 4. Four strips of double-sided adhesive are included for each panel. Apply the tape strips to textured side of black or white panel and smooth side of brushed stainless panel as follows:
 - Lay out tape strips according to illustration at left.
 - Remove one strip and apply to either right or left side to start.
 - Press each tape strip firmly onto the plastic as it is applied.
 - Continue until all 4 strips are applied.
- Note: Alignment is critical. Once placed on the wall, the Wall Guard cannot be re-positioned.**
5. Align the top edge of the Wall Guard with the markings on the wall and firmly press into place against the entire surface of the Wall Guard.
 6. Optional: After guard is applied to the wall you may add silicone sealant around the edge.

CLEANING INSTRUCTIONS

Clean the installed Wall Guard with mild soapy water and a soft cloth. Mild dish soap mixed with water in a spray bottle works best.

DO NOT USE any cleaner that contains any ammonia or abrasive cleansers to clean the surface.



TIME TO THROW IN THE TOWEL®

ALLIED HAND DRYER, LLC
San Antonio, TX

1.800.535.4393
1.210.733.5918

www.handdryer.com
sales@handdryer.com

JAN
2017

16WGS0009