

## Hand Dryer Series

**Description:HK-1800PA**

Automatic operation hand dryer  
 Casing:made of high grade fire retardant  
 ABS, 3.0 mm thick  
 Brush motor:80W,2850 R.P.M.(50Hz)  
 3400 R.P.M.(60Hz)  
 Heater assembly:  
 Designed with 105° C(221° F)thermostat.  
 Designed with 87° C(200° F)thermostat.  
 Designed with 141° C(323° F)thermal cut-off.  
 Sound level:55 ± 3db  
 Air speed:16.5m/s--60Hz 14.5m/s--50Hz  
 Approximately 30-35 seconds drying time.



Dryer shall deliver 291 m<sup>3</sup>/h(171CFM)–60Hz. 255 m<sup>3</sup>/h(150CFM)–50Hz.  
 Adjustable timer control range from 10 to 30 seconds.  
 Power cut off automatically in case of irregular use over 120 seconds.  
 Drip proof:IPX1  
 WEIGHT: 3.8 kgs (8.4lbs) unpacked :4.5 kgs (9.9lbs) packed.

**Specifications and Dimensions**

Model	Volts	Watts	Amps	W	Housing Dimension : mm (in)	
					H	D
HK-1800PA	120Vac	1800W	15A	268(10 1/2)	220(8 3/4)	170(6 3/4)
	220Vac	1800W	8.2A	268(10 1/2)	220(8 3/4)	170(6 3/4)
	230/240Vac	1653-1800W	7.2-7.5A	268(10 1/2)	220(8 3/4)	170(6 3/4)



